

# Xpelair BriteX LoVolt & Turbo inline fans

Inline shower fan and SELV light systems for shower cubicles



## The Range

Xpelair BriteX range is designed to extract condensation laden air directly from above the shower whilst bathing the cubicle in warm light. Xpelair BriteX kits include everything needed for a standard installation including a stylish ceiling inlet complete with bezel and 12V 35W sealed dichroic lamp, an inline extract fan, 12V Safety Extra Low Voltage (SELV) transformer, flexible ducting, duct ties and a soffit/wall grille. The kits are available in a choice of white or chrome bezel. For larger shower rooms and longer ducts choose BriteX Turbo which comes complete with 6 metres of flexible ducting. The motor housing is made from ABS and has a detachable mounting foot.

## Key Features

- All models available with white or chrome finished internal bezel
- Supplied with 12V 35W sealed dichroic lamp and inline transformer
- Lubricated for life, maintenance free motors with thermal cut-out protection
- IPX4 rated

## Models

**XPEBX100C** CHROME

**XPEBX100W** WHITE

BX100 (16 l/s) supplied with 3m of flexible ducting

**XPEBX100+ C** TURBO CHROME

**XPEBX100+ W** TURBO WHITE

BX100+ turbo (21 l/s) supplied with 6m of flexible ducting

Product Selector	BX100W	BX100C	BX100+ W	BX100+ C
Reference number	92276AW	92278AW	91248AW	91249AW
Duct length (supplied)	3m	3m	6m	6m
Fan electrical power rating (W)	30	30	25	25
Hole diameter (mm)	102	102	102	102
IP rating	IPX4	IPX4	IPX4	IPX4
Colour	white	chrome	white	chrome
Weight (kg)	0.5	0.5	2.1	2.1
Extract performance (m <sup>3</sup> /h)	58	58	74	74
Extract performance (l/s)	16	16	21	21
Duct length (supplied)	3m	3m	6m	6m
Sound pressure level (dB(A)@ 3m)	36	36	55	55
Guarantee (years) (excludes lamp)	1	1	1	1